POST PRINTING PAPER FINISHING SYSTEMS Cost-Efficient Solution for Paper gathering Demands

• DFC-120/ DFC-101 Collator

Duplo

from print to documents





Specifications

DBM-150, DBM-150T

DBM-150 Stacker

Booklet size Saddle stapling

and folding Paper type

Stapling Thickness

Max processing speed

Trmming waste width

Number of sheets that

Stapler

Stapling width

can be trimmed





DFC-S (Corner & Side Stapler Unit)

DFC-120/DFC-101 Stacker

DFC-120/DFC-101

Model Type	Friction feed vertical collator
No. of bins	12 bins/10 bins
Paper Size	Max: A3SR (320 x 450 mm) MIN : A5 (140 mm x 160 mm)
Paper Type	Medium quality paper, Fine porous paper, fine quality paper (52.3 to 128 Gsm)
Paper feed bin capacity	28 mm equivalent to Fine quality paper 64 Gsm, 350 Sheets
Maximum Process Speed	70 Sets/Min. 120 [*] Sets/Min. (A4 long edge feed) * Available with DFC-101 only
Paper Stack	Straight, Offset
Paper Stack Capacity	Max. 80 mm (The height of full detection sensor is 65 mm)
LCD	4 Digi counter (Count up/Count down)
Paper feed error detection	Empty feed, double feed, paper jam
Additional Functions	Offset/Straight stacking, Interleave insertion, Block Mode feeding, Paper ejection, ALT. mode
Power Supply	AC 100-240V, 50/60 Hz
Power Consumption	1.2-0.8 A 145W (Approx.)
Weight	65 Kg
Options	Cabinet/Trolly, DFC-S Stapler Unit, DBM-150 Booklet maker & 150T Trimmer

Duplo is a trade mark of the Duplo Corporation. Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions. As part of our continuous product improvement program, specifications are subject to change without notice.



Duplo Corporation, 4-1-6 Oyama, Chuo-Ku, Sagamihara-Shi, Kanagawa, 25 25 280, Japan

Staple capecity	5,000 staples per cartridge
Operation panel	LCD control panel (DBM-150)
Noise emission	Equivalent continuous A-Weighted sound pressure level: 75.2 - Sound Pressure level: 92.5
Power supply	120 to 240 V 50/60 Hz
Current consumption	DBM-150: 130W 1.2-07A DBM-150 +DBM- 150T: 230W 2.2-1.1A
Net weght	137Kg
Specifications DFC-S (Corner & Side Stapler Unit)	

Length 210 to 450 mm Width 148 to 320 mm

with in 300 gsm

2400 sets/hour

1 to 20 mm

4 to 50 sheets

Fine quality: 64 to 127.9gsm, Art/Coated: 104.7 to 127.9 gsm Cover: Fine quality, Art/Coated

Fine Quality: within 2.5mm (Maximum of 25 sheets) Art/Coated: with in 2.0mm (Maximum of 20 sheets)

ISABERG RAPID R952

70, 108, 160 258, and 276mm

Paper Size Max: A3, Min. A5 Speed 25/35/40 Sets per minute (Selectable from the collator) Operations Corner, Counter Corner and Side Stapling **Staple Capacity** 2-24 Sheets, (52.3 to 81.4 Gsm)/ 2-15 Sheets (52.3 to 127.9 Gsm)

TECHMART

Authorised Indian Disrtibutor : TECHMART DIGITAL SYSTEMS PVT. LTD. 4/14, IInd Floor, Kirti Nagar Industrial Area New Delhi-110015 Tel No.: 011-4515 1888, 45151899 E-mail: info@techmartdigital.com www.techmartdigital.com

> Product is available at all India through dealer network and our branches:-New Delhi, Chandigarh, Lucknow, Indore, Jabalpur, Ahmedabad, Ranchi, Patna, Kolkatta